

Alpha XD



Servo self leveling, high performance, rugged design and extreme distance.

When taking extremely long grade shots is a must, the Pro Shot™ Alpha XD laser level tool delivers the industry leading performance you need. All of the great features and specs from the standard Alpha, plus a **3300ft (1km)** radius coverage area.

Specifications

XD range - R9 laser receiver .	3300' dia., 1650' rad. (1km/500m)
Accuracy	± 10 arc sec. (± 1/16" per 100')
	(± 1.5mm per 30m)
Self leveling type • Range	Servo motor • ± 5 degrees
Slope matching • Range	Single axis, X-axis self-leveled • 8%
Height alert	Normally active, can be disabled
Rotation coverage • speed	360° • 600 or 1200rpm, selectable
Machine control compatible ...	Yes, including high speed rotation
Warranty.....	24 Month defects coverage
Power source • Life	Four C-cells • 90 hrs. (alkaline)
Rechargeable batts. • Life	Optional Ni-Mh kit • 65 hrs.
Laser beam type	Visible 670nm
XD Laser classification	CDRH class IIIa • IEC class 3R
Dust and water sealed	To international standard IP56
Operating temperature	-4° F to +140° F (-20° C to +60° C)
Built to be jobsite tough	Designed to withstand a 3ft (1m) drop or 5ft (1.5m) tripod knock-over on concrete

Alpha XD system including R9 receiver and carrying case
\$920.00 US list price

[Alpha brochure PDF](#)

[Alpha XD manual PDF](#)

[Accessories Page](#)

Is the Pro Shot Alpha the toughest, most dependable laser you can buy? Watch this video and decide for yourself...

[Alpha durability test video](#)



[Email sales@proshotlaser.com](mailto:sales@proshotlaser.com)

Laser Reference, Inc. • USA Toll Free 1.800.238.0685